

MAXIMIZE YOUR TIME
INCREASE YOUR PERFORMANCE

ELTOR EVO



INDUSTRIAL TYRES

MARANGONI ™

ELTOR EVO

The technology that anticipates tomorrow by 10%

Our prime objective? To extend tyre life and save our customers time and money, without compromising on performance. Rather, improving performance even more compared to similar competing products.


Marangoni's response has a name: **Eltor EVO**. This new range can withstand a high number of working hours (10% more compared to other premium products) by generating less heat, the result of a new structure and optimised characteristics of the compounds.

The results achieved today with Eltor EVO in terms of reliability, performance and safety were unconceivable just a few years ago.

BENEFITS OF ELTOR EVO

LOWER ROLLING RESISTANCE

-8%*



LOWER ENERGY CONSUMPTION

-20%*




REDUCED HEAT PRODUCTION

-15%*



LONGER LIFE

+10%*



Longer continuous service without stopping for maintenance means savings in terms of **time and costs**, as well as **reducing environmental impact**. Less replacements mean less CO2 emissions, beneficial for the environment.

* Tests conducted in the laboratory with other premium products.

ELTOR EVO

more time, more **EVOLution**



Industrial tyres have a significant influence on vehicle efficiency. Energy consumption, smooth running and friction coefficient are the fundamental parameters used to test rolling resistance.

Low rolling resistance means lower battery power, less fuel consumption and a low tyre working temperature. In other words, consistent performance and minimum tyre wear.

The major competitive advantage of **Eltor EVO** comes from the development of optimised compounds, produced exclusively using the best raw materials allowed by European Union directives.

New tread structure, with the 60J positioned on a smaller diameter
= longer life compared to other premium products

Compounds designed for better rolling resistance and less friction between the tread and the ground
= lower energy consumption and maximum battery efficiency



GOOD DIRECTIONALITY



BETTER TRACTION



GREATER STABILITY SMOOTH RUNNING



SUPER-ELASTIC **ELTOR EVO**



Ø	TYRE SIZE (INCHES)	PROFILE	RIM SIZE	TYRE DIMENSIONS (1)		WEIGHT (kg) ± 2%	LOAD CAPACITY (KG) AT MAX SPEED (KM/H) (2)					
				W (mm) ± 2%	D (mm) ± 2%		CARRYING WHEEL 25 km/h	STEERING WHEEL 25 km/h	TRAILERS (3)			
							25 km/h	25 km/h	25 km/h	10 km/h	6 km/h	
8"	5.00-8	EVO	3.00D-8	120	458	17,1	1.415	1.090	1.090	1.285	1.415	
	5.00-8	EVO FIX	3.00D-8	120	458	17,2	1.415	1.090	1.090	1.285	1.415	
	15x4½-8 (125/75-8)	EVO	3.00D-8	109	377	9,4	1.040	800	800	940	1.040	
	15x4½-8 (125/75-8)	EVO FIX	3.00D-8	109	377	9,7	1.040	800	800	940	1.040	
	16x6-8 (150/75-8)	EVO	4.33R-8	151	421	17,1	1.495	1.150	1.150	1.360	1.495	
	16x6-8 (150/75-8)	EVO FIX	4.33R-8	151	421	17,4	1.495	1.150	1.150	1.360	1.495	
	18x7-8 (180/70-8)	EVO	4.33R-8	152	453	20,2	2.145	1.650	1.650	1.945	2.145	
	18x7-8 (180/70-8)	EVO FIX	4.33R-8	152	453	20,5	2.145	1.650	1.650	1.945	2.145	
9"	140/55-9	EVO FIX	4.00E-9	130	380	11,8	1.170	900	900	1.060	1.170	
	6.00-9	EVO	4.00E-9	139	525	26,1	1.885	1.450	1.450	1.710	1.885	
	6.00-9	EVO FIX	4.00E-9	139	525	26,4	1.885	1.450	1.450	1.710	1.885	
	21x8-9 (200/75-9)	EVO	6.00E-9	183	522	34,2	2.755	2.120	2.120	2.505	2.755	
	21x8-9 (200/75-9)	EVO FIX	6.00E-9	183	522	34,6	2.755	2.120	2.120	2.505	2.755	
10"	180/60-10	EVO	5.00F-10	152	454	18,5	2.410	1.850	1.850	2.180	2.410	
	180/60-10	EVO FIX	5.00F-10	152	454	19,0	2.410	1.850	1.850	2.180	2.410	
	6.50-10	EVO	5.00F-10	160	575	36,6	2.340	1.800	1.800	2.125	2.340	
	6.50-10	EVO FIX	5.00F-10	160	575	36,8	2.340	1.800	1.800	2.125	2.340	
	7.50-10	EVO	5.50F-10	176	636	52,3	3.070	2.360	2.360	2.785	3.070	
	7.50-10	EVO FIX	5.50F-10	176	636	52,3	3.070	2.360	2.360	2.785	3.070	
	200/50-10	EVO	6.50F-10	189	464	25,6	2.470	1.900	1.900	2.240	2.470	
	200/50-10	EVO FIX	6.50F-10	189	464	26,1	2.470	1.900	1.900	2.240	2.470	
	23x9-10 (225/75-10)	EVO	6.50F-10	195	581	46,0	3.445	2.650	2.650	3.125	3.445	
	23x9-10 (225/75-10)	EVO FIX	6.50F-10	195	581	46,3	3.445	2.650	2.650	3.125	3.445	
	12"	7.00-12	EVO	5.00S-12	169	658	47,6	2.920	2.240	2.240	2.645	2.920
		7.00-12	EVO FIX	5.00S-12	169	658	48,3	2.920	2.240	2.240	2.645	2.920
23x10-12		EVO	8.00G-12	227	586	49,9	3.770	2.900	2.900	3.420	3.770	
23x10-12		EVO FIX	8.00G-12	227	586	50,6	3.770	2.900	2.900	3.420	3.770	
27x10-12		EVO	8.00G-12	235	672	73,5	3.900	3.000	3.000	3.450	3.900	
27x10-12		EVO FIX	8.00G-12	235	672	74,3	3.900	3.000	3.000	3.450	3.900	
315/45-12		EVO	10.00G-12	275	588	61,0	4.485	3.450	3.450	4.070	4.485	
315/45-12		EVO FIX	10.00G-12	285	574	61,4	4.485	3.450	3.450	4.070	4.485	
15"		250-15 (250/70-15)	EVO	7.0-15	214	721	66,5	4.750	3.650	3.650	4.300	4.750
		250-15 (250/70-15)	EVO FIX	7.0-15	214	721	67,0	4.750	3.650	3.650	4.300	4.750
	250-15 (250/70-15)	EVO	7.5-15	214	721	67,5	4.750	3.650	3.650	4.300	4.750	
	250-15 (250/70-15)	EVO FIX	7.5-15	214	721	68,5	4.750	3.650	3.650	4.300	4.750	
	7.00-15	EVO	5.5-15	180	728	59,0	3.545	2.725	2.725	3.215	3.545	
	7.00-15	EVO FIX	5.5-15	180	728	59,5	3.545	2.725	2.725	3.215	3.545	
	7.50-15	EVO	5.5-15	205	758	72,2	3.880	2.980	2.980	3.510	3.880	
	7.50-15	EVO FIX	5.5-15	205	758	72,7	3.880	2.980	2.980	3.510	3.880	
	7.50-15	EVO	6.5-15	205	758	72,9	3.900	3.000	3.000	3.540	3.900	
	7.50-15	EVO FIX	6.5-15	205	758	74,2	3.900	3.000	3.000	3.540	3.900	
	28x9-15 (8.15-15)	EVO	7.0-15	214	699	61,8	3.445	2.650	2.650	3.125	3.445	
	28x9-15 (8.15-15)	EVO FIX	7.0-15	214	699	62,2	3.445	2.650	2.650	3.125	3.445	
	28x12½-15	EVO	9.75-15	285	716	91,0	5.525	4.250	4.250	5.015	5.525	
	28x12½-15	EVO FIX	9.75-15	285	716	92,0	5.525	4.250	4.250	5.015	5.525	
	8.25-15	EVO	6.5-15	203	822	90,9	4.750	3.650	3.650	4.300	4.750	
	8.25-15	EVO FIX	6.5-15	203	822	92,4	4.750	3.650	3.650	4.300	4.750	
	300-15 (315/70-15)	EVO	8.0-15	256	821	114,0	5.850	4.500	4.500	5.310	5.850	
	300-15 (315/70-15)	EVO FIX	8.0-15	256	821	114,9	5.850	4.500	4.500	5.310	5.850	
355/65-15 (350-15)	EVO	9.75-15	300	821	135,2	7.800	6.000	6.000	7.085	7.800		
355/65-15 (350-15)	EVO FIX	9.75-15	300	821	136,1	7.800	6.000	6.000	7.085	7.800		

(1) Sizes are intended for tyres not fitted on rims;
 (2) Capacity values indicated are in reference to ELTOR tyres mounted on vehicles whose speed with no cargo is less than 25 km/h (according to E.T.R.T.O. standards);
 (3) Only for interior courses inferior to 2.000 metres; if otherwise, contact dealer (according to E.T.R.T.O. standards).





Marangoni S.p.A.
Via del Garda, 6
38068 Rovereto (TN) Italy
Tel. +39 0464 301111
Fax +39 0464 301123
industrial.tyres@marangoni.com
industrial.marangoni.com

MARANGONI ™